

# CLEAN **UP**

*with Graco®*

## Hydra-Clean Pressure Washers



*Bulldog® 10:1 Cart Mount*

- Fits most pressure, flow and material requirements
- Use with open-head universal drums
- Designed to use with cold or hot water up to 200°F (93°C)
- Available with an accumulator and chemical injector
- Spray down portability for use in sanitary applications
- Efficient cleaning with water, detergent or chemical solutions
- Supports multiple guns

**For more information visit**  
[www.graco.com/hydraclean](http://www.graco.com/hydraclean)  
**or call us at 1-877-844-7226**



# Technical Specifications

Part Number	Pump Package	Max. Working Pressure psi (MPa, bar)	Max. Air Input Pressure psi (MPa, bar)	Fluid Flow at 60 cpm gpm (lpm)	Vol. per Cycle oz (cc)	Air Inlet Size	Fluid Inlet Size	Fluid Outlet Size	Package Instruction Manual
206515	President 10:1	1000 (7, 69)	100 (0.7, 7)	3 gpm (11.4)	6.4 (189)	1/2 npt(f)	3/4 npt(f)	1/2 npt(f)	306817
226314	Bulldog 10:1	1000 (7, 69)	100 (0.7, 7)	8 (29)	17 (505)	3/4 npsm(f)	2 npt(f)	1-1/2 npt(m)	306926 308509
965389	Premier 34:1	3400 (23, 230)	100 (0.7, 7)	9.2 (34.8)	19.6	3/4 npsm(f)	2 npt(f)	1-1/2 npt(m)	308152

## Ordering Information

Package Order No.	President 10:1 206515	Bulldog 10:1 226314	Premier 34:1 965389
Pump Assembly Part No.	224346	206797	-
Pump Lower Part No.	224344	206792	222994
Construction	SST	SST	SST
Standard Seal Repair Kits	224402	207581	222876
Construction	UHMWPE/Neoprene	PTFE	PTFE
Optional Seal Repair Kits	224404	N/A	222875
Construction	UHMWPE/PTFE		UHMWPE/PTFE
Motor Repair Kit	207385	206734	222958

## Accessories

### GUNS AND TIPS

- 208008** Spray gun with 10 in (254 mm) wand
- 244784** Spray gun with 32 in (813 mm) wand
- 207299** 10 in (254 mm) replacement wand

### WHIP HOSES

- Maximum working pressure: 3000 psi (20.7 MPa, 207 bar). ID 3/16 in (5 mm).
- 238358** 3 ft (0.9 m), 1/4 npsm(f) x 1/4 npt(m)  
Maximum working pressure: 5000 psi (34.5 MPa, 345 bar). ID 1/4 in (0.63 cm), 1/4 npsm(fbe).
- H52503** 3 ft (0.9 m)
- H52506** 6 ft (1.8 m)



President® 10:1 Open Drum Mount

## Tip Selection Chart

### BLASTING TIPS AND STAINLESS STEEL

Part No.	Tip No.	Orifice Size in. (mm)	Flow Rate at 500 psi (35 bar, 0.35 MPa) gpm (lpm)
102446	0010ss (SST)	0.086 (2.18)	3.5 (13.2)
102450	0020ss (SST)	0.125 (3.18)	7.1 (27.0)

### STAINLESS STEEL

Part No.	Tip No.	Orifice Size in. (mm)	Fan Width Angle at 40 psi (3 bar, 0.03 MPa)	Capacity at 500 psi (35 bar, 0.35 MPa) gpm (lpm)
160959	4001	0.26 (0.66)	40°	.35 (1.3)
160970	15015	0.031 (0.79)	15°	.53 (2.0)
160965	25015	0.031 (0.79)	25°	.53 (2.0)
160958	4002	0.036 (0.91)	40°	.71 (2.7)
160964	2503	0.043 (1.09)	25°	1.1 (4.2)
160963	2506	0.062 (1.57)	25°	2.1 (7.9)
103921	6540	0.065 (1.57)	40°	2.3 (8.0)
165477	2510	0.078 (1.98)	25°	3.5 (13.2)
165090	4010	0.078 (1.98)	40°	3.5 (13.2)
165089	2515	0.0937 (2.38)	25°	5.3 (20.1)
160968	1520	0.1093 (2.78)	15°	7.5 (28.4)
160962	2520	0.1093 (2.78)	25°	7.5 (28.4)
160956	4020	0.1093 (2.78)	40°	7.5 (28.4)



Premier® 34:1 Cart Mount